

N 30, INTEGRATED COOKER HOOD, 60 CM, SILVER
D61MAC1X0B



D

Z51IMA0X0 Standard odor filter (replacement)

The Integrated Cooker Hood with a fold out unit is discreetly hidden within the upper cabinets.

- ✓ LED Lighting – Clear illumination while you cook.
- ✓ Reduced Noise: our optimised motor guarantees a quiet cooking experience.

Typology: Built-in/Built-under
 Length electrical supply cord: 150.0 cm
 Minimum distance above an electric hob: 500 mm
 Minimum distance above a gas hob: 650 mm
 Net weight: 10.3 kg
 Type of control: mechanical
 Number of speed settings: 3
 Maximum output air extraction: 368 m³/h
 Maximum output recirculating air: 272 m³/h
 Maximum Air flow: 368 m³/h
 Number of lights: 2
 Noise level: 62 dB(A) re 1pW
 Diameter of air outlet: 150 / 120 mm
 Grease filter material: Washable aluminium
 EAN code: 4242004223351
 Connection Rating: 126 W
 Fuse protection: 10 A
 Voltage: 220-240 V
 Frequency: 50; 60 Hz
 Plug type: GB plug
 Installation typology: Wall-mounted



4 242004 223351

N 30, INTEGRATED COOKER HOOD, 60 CM, SILVER D61MAC1X0B

Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 368 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 62 dB dB*

Features

- Push button control operation
- 3 power levels
- 2 x 3W LED
- Colour Temperature: 2700 K
- 2 metal grease filter cassettes
- Installation: Between Cupboards

Design

- Integrated hood
- Hinged door
- Mechanical controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction charcoal filter (accessory) needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 62 dB(A) re 1 pW
- Power rating: 126 W
- Light Intensity: 188 lux
- Electrical cable length 1.5 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating (HxWxD): 402-402 x 599 x 271 mm
- Blower Efficiency Class: E*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 65.7 kWh/year*

Optional accessories

- Recirculating kit Z511MA0X0

* In accordance with the EU-Regulation No 65/2014

N 30, INTEGRATED COOKER HOOD, 60 CM, SILVER
D61MAC1X0B

