

**Series 2, Wall-mounted cooker hood,  
60 cm, Stainless steel  
DWP64CC50M**



**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

- **Silent:** maximum extractor performance with minimal noise.
- **3-speed power Level options to suit your cooking style and recipes.**
- **Dishwasher safe aluminum mesh filters**
- **Ducted or Non-ducted Options**

DWA0KP6A Standard odor filter  
DWZ6HP1U2 Standard recirculation kit

Typology: .....Wall-mounted  
 Length electrical supply cord: ..... 120.0 cm  
 Height of the chimney: ..... 410-765/410-765 mm  
 Height of the appliance: ..... 250 mm  
 Minimum distance above an electric hob: ..... 650 mm  
 Minimum distance above a gas hob: .....650 mm  
 Net weight: .....9.2 kg  
 Type of control: .....mechanical  
 Number of speed settings: ..... 3  
 Max. air extraction: .....380 m<sup>3</sup>/h  
 Max. air recirculation: ..... 235 m<sup>3</sup>/h  
 Maximum Air flow: .....380 m<sup>3</sup>/h  
 Number of lights: ..... 2  
 Noise level: .....64 dB(A) re 1pW  
 Diameter of air outlet: ..... 150 mm  
 Grease filter material: .....Washable aluminium  
 EAN code: .....4242002985299  
 Connection rating: ..... 135 W  
 Voltage: ..... 220-240 V  
 Frequency: ..... 50 Hz  
 Plug type: ..... GB plug  
 Installation typology: .....Wall-mounted



4 242002 985299

## Series 2, Wall-mounted cooker hood, 60 cm, Stainless steel DWP64CC50M

**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

### Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 380 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 64 dB dB\*

### Features

- 3 power levels
- 2 x LED 5W
- Colour Temperature: 4000 K
- 2 removable metal grease filter cassettes
- Installation: wall

### Design

- Chimney extractor hood
- Push button control
- Mechanical

### Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction charcoal filter (accessory) needed
- Maximum extraction rate exhaust air 380 m<sup>3</sup>/h according to EN 61591
- Extraction rate in recirculation mode:
  - Max. normal use: 235 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW
- Noise level in recirculation mode:
  - Max. normal use: 70 dB(A) re 1 pW (56 dB(A) re 20 µPa sound pressure)
- Power rating: 135 W
- Light Intensity: 1000 lux
- Electrical cable length 1.2 m
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Dimensions exhaust air (HxWxD): 790-1015 x 598 x 470 mm
- Dimensions recirculating (HxWxD): 790-1015 x 598 x 470 mm
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 72.8 kWh/year\*

### Optional accessories

- Recirculating kit DWA0KP6A

\* In accordance with the EU-Regulation No 65/2014

**Series 2, Wall-mounted cooker hood,  
60 cm, Stainless steel  
DWP64CC50M**

