



L I S S E R F L U S H

THIS LISSER FLUSH IS EXTREMELY DISCREET IN DESIGN AND RETRACTS FULLY INTO THE WORKTOP FOR A FLUSH FINISH.

WIDTH	575MM, 875MM OR 1175MM
DEPTH	120MM
HEIGHT	742 + 300MM MAX EXTENSION
FINISH	STAINLESS STEEL OR BLACK GLASS
CONTROLS	4 SPEED PUSH TOUCH CONTROL
LIGHTING	1X 6.5W LED (575 MODEL) 1X 5W LED (875 MODEL) 1X 9W LED (1175 MODEL)
FILTERS	CONCEALED ALUMINIUM MESH, SUITABLE FOR DISHWASHERS
DUCT POSITION	LEFT, RIGHT, FRONT, REAR OR DOWN
MOTOR OPTION	INTERNAL, REMOTE OR RECIRCULATING



ENERGY RATING (BOLT ON MOTOR)



ENERGY RATING (REMOTE MOTOR)



AIRFLOW RATING (BOLT ON MOTOR)

800 CMPH

MAXIMUM DB LEVEL (SPEED 4 - BOOST)

68DB (INTERNAL MOTOR)

POWER SUPPLY REQUIREMENT

3 AMP (INTERNAL)
5 AMP (REMOTE)

CUTOUT SIZE

542MM/ 842MM/1142MM X 100MM

