

IRBAc 5190

Integratable refrigerator with BioFresh Professional and AutoDoor


△ Peak

↑
178
↓



G Made in Germany



| | |
|---------------------------------------|---|
| Type | Fixed door / Built-in appliance for integrated use |
| Energy efficiency class |  |
| Energy consump. in 365 days/24 h | 100 / 0.274 kWh |
| Total volume | 296 l ¹ |
| Volume | Fridge: 198.1 l / BioFresh compartment: 97.9 l |
| Noise output / noise class | 32 dB(A) / B, SuperSilent |
| Climate rating | SN-T (+10 °C to +43 °C) |
| Frequency / voltage | 50-60 Hz / 220-240 V~ |
| Connection Rating | 1.2 A |
| Aperture dimensions in cm (h / w / d) | 177.2-178.8 / 56-57 / min. 55 |
| Door hinges | IRBAc 5190-001 opens to right IRBAc 5190-617 opens to left |
| Controls | |
| Type of Control | 2.4" TFT-colour display, touch- & swipe Digital temperature display for fridge and BioFresh compartments |
| Interface | SmartDeviceBox included |
| Door alarm | visual and acoustic |
| Fridge compartment | |
| Forced air system | PowerCooling with Ambilight and FreshAir activated charcoal filter |
| Door interior | Premium GlassLine storage shelves with bottle holder, removable VarioBoxes, adjustable egg tray, butter dish |
| VarioSafe | yes |
| Bottle shelf | Integrated bottle shelf |
| Interior light | LED light panel, both sides LED BioFresh lighting |
| BioFresh-Safes | 3 BioFresh safes with SoftTelescopic, 2 Fruit & Vegetable safes, of which 1 with HydroBreeze, 1 Meat & Dairy safe, 1 FlexSystem |
| Features | |
| Door hinges | Reversible door hinging right |
| Replaceable door seal | yes |
| EAN-Nr. | 4016803114659 |

¹ In accordance with Regulation EU 2019/2016 we indicate the total volume to the nearest integer (rounded off) and the volume of the frozen compartments and refrigeration compartments to one place after the decimal point.

SIFNAd 5188

Integratable freezer with NoFrost and AutoDoor

△ Peak

↑
178
↓



G Made in Germany



Smart Device

| | |
|---------------------------------------|---|
| Type | Fixed door / Built-in appliance for integrated use |
| Energy efficiency class | |
| Energy consump. in 365 days/24 h | 190 / 0.520 kWh |
| Total volume | 213 l ¹ |
| Noise output / noise class | 33 dB(A) / B, SuperSilent |
| Climate rating | SN-T (+10 °C to +43 °C) |
| Frequency / voltage | 50-60 Hz / 220-240 V~ |
| Connection Rating | 1.3 A 186 W |
| Aperture dimensions in cm (h / w / d) | 177.2-178.8 / 56-57 / min. 55 |
| Door hinges | SIFNAd 5188-001 opens to right SIFNAd 5188-617 opens to left |
| Controls | |
| Type of Control | 2.4" TFT-colour display, touch- & swipe Digital temperature display |
| Interface | SmartDeviceBox included |
| Door alarm | visual and acoustic |
| Alarm in case of malfunction | visual and acoustic |
| Freezer compartment | |
| Star coding | **** |
| Interior light | LED lighting |
| Number of drawers | 8 drawers, davon 5 mit Teilauszug auf Teleskopschienen, VarioSpace |
| IceMaker | with fixed 3/4" water connection, LED lighting |
| Ice cube capacity in 24 hours | 0.8 kg |
| Ice cube stock | 5.7 kg |
| Freezing capacity in 24 hours | 12 kg |
| Temperature rise time | 9 h |
| VarioSpace | yes |
| Cold storage accumulators | 2 |
| Features | |
| Side-by-Side concept | Side-panel heating on both sides, suitable for combination with other fridges, freezers and/or wine appliances |
| Door hinges | Reversible door hinge, left |
| Replaceable door seal | yes |
| EAN-Nr. | 4016803115694 |

¹ In accordance with Regulation EU 2019/2016 we indicate the total volume to the nearest integer (rounded off) and the volume of the frozen compartments and refrigeration compartments to one place after the decimal point.